

# Processor II



# COMMERCIAL



## Specification

**Carpet Description**  
Patterned Loop Pile Graphic

**Fibre Content**  
100% Permatex® Solution Dyed Nylon

**Machine Gauge (AS2111.9)**  
39.4/10cm (1/10th)

**Finished Pile Height (AS2111.5)**  
3.8mm (+/- 1mm)

**Pile Weight (AS2111.11)**  
680g/m<sup>2</sup> (20oz/yd<sup>2</sup>)

**Carpet Width**  
3.66 metres (12ft)

**ECS Grading**  
Level 4

**ACCS Grading**  
Contract Extra Heavy Duty & Stairs  
Residential Extra Heavy Duty & Stairs

**ECS/ACCS Registration**  
28235

**Pattern Match**  
45mm width x 45mm length

**Flammability\* (ISO9239 - 1:2003)**  
Result - Mean 6.9 kw/m (Direct Stick)  
Smoke Value 27% min (Direct Stick)  
Result - Mean 2.4 kw/m (Conventionally Laid)  
Smoke Value 310% min (Conventionally Laid)

**Tolerances**  
As per AS 1385 or +/- 5% whichever is greater

## INSTALLATION

All carpet should be installed in accordance with Australian/NZ Standards Association Carpet Installation Recommendations AS/NZ2455-2007 and any other instructions/recommendations provided by Feltex Carpets unless otherwise specified.

## MAINTENANCE

Carpet should be cleaned and maintained in accordance with AS/NZS 3733/1995-1, and or as instructed by Feltex Carpets.

## COLOUR VARIATION

Shade or pattern may vary from sample and between dyelots and within production runs due to normal dyelot variation but will be within recognised textile industry standards. Colour appearance can also vary depending upon type of light under which a sample is viewed and the light sources where the carpet is installed.

## PERMANENT PILE REVERSAL (Shading / Puddling / Watermarking)

Light can play strange tricks with carpet, making it appear from certain angles that particular areas are lighter or darker than others. Known as shading, it is due to the pressure on the pile during use, causing pile to lay in different directions resulting in light refraction and is a feature characteristic of cut pile carpets (particularly solid colour). Apart from affecting appearance, it has no detrimental effect on the performance of the carpet.

## PATTERNED CARPETS

While Feltex Carpets uses the best available techniques to minimise pattern distortion during manufacture, the extensible nature of textile products means that some distortion due to shrinkage or stretch during and after manufacture is unavoidable, such that perfect pattern match cannot be guaranteed. Installation of patterned carpet will require more time, effort and skill and a competent carpet layer should be able to obtain a close pattern match in most circumstances though some irregularities may still be visible, particularly over multiple width installations. We further suggest you discuss pattern matching with your installer.

## PANELLING / PHASING

An effect known as phasing can occur where carpet design includes random use of contrasting colours when at times these colours can coincide in production. Similarly in loop pile carpets, shading effects of colour patterning can appear as panelling down the length of the carpet. Both phasing and panelling are an accepted part of the design and in no way affect the carpet's performance.

## SHIFT LINES

Construction of this carpet may involve the occurrence of shift lines across the width of the carpet. Colour, directional pile lay and light sources shining across the carpet may accentuate these lines in the form of shadowing. This is not a manufacturing fault and will not affect the carpet's wear or durability.

All product specifications and colourations are subject to normal manufacturing tolerances. As part of Feltex Carpets' continuous improvement program, Feltex Carpets reserves the right to change the specifications of or delete colours of this product without notice.

\*Test results available upon request

## How to order

For samples and sales, contact your local sales office or visit our website  
[www.feltex.com](http://www.feltex.com)  
[www.feltex.co.nz](http://www.feltex.co.nz)

## Sales Offices

**Melbourne**  
2 Gilbertson Road  
Laverton North VIC 3026  
T +61 3 9368 8100

**Sydney**  
28 Percival Road  
Smithfield NSW 2164  
T +61 2 8784 8700

**Brisbane**  
33 Gassman Drive  
Yatala QLD 4207  
T +61 7 3804 5155

**Perth**  
Unit 3 / 81 Guthrie Street  
Osborne Park WA 6017  
T +61 8 9242 7643

**Adelaide**  
Unit 12, 60-66 Richmond Rd  
Keswick SA 5035  
T +61 8 8371 1711

## Head Office

T 1300 130 239  
F 1800 654 595  
[feedback@feltex.com](mailto:feedback@feltex.com)

## International Offices

**New Zealand**  
84 Kerrs Road, Wiri  
Manukau City 2104  
Auckland, New Zealand  
T (freephone) 0800 100 008

**Singapore**  
200 Jalan Sultan  
#07-310 Textile Centre  
Singapore 199018  
T +656 841 5529



Pictured 31/- Armour Blue  
Attached 44/- After Dark



Meets Green Label Plus Specifications



Manufactured under an environmental, quality and health and safety system certified and complying with ISO14001, ISO9001 and AS4801 by accredited certification bodies.